

tesa® 4657

Temperature resistant acrylic coated cloth tape

PRODUCT INFORMATION

Product Description

tesa® 4657 is a high grade acrylic coated cloth tape. It is based on a 145 mesh woven cotton fabric and a thermosetting natural rubber adhesive.

tesa® 4657 is a very resilient cloth tape often used for permanent hole covering in automotive applications and masking during industrial painting processes.

Features:

- removable without residues even after high temperature exposure
- very ageing-resistant (allowing for permanent applications)
- high resistance to paint solvents
- excellent tape for die-cuts, available as log roll with liner as tesa® 4657 PV9
- also available as low unwinding version tesa® 4657 PV 1
- available in 2 colors: black, grey

Main Application

- Heat resistant masking during the production of vehicles and machines
- Window flange masking
- Even repeated oven drying possible
- Permanent interior and exterior hole covering
- Covering of screw tap holes and drainage boreholes
- Partial masking during treatment with impregnating agents
- Fastening of flat cables e.g. on roof linings, door panels, mirrors
- Masking during electrostatic powder coating

Technical Data

■ Backing material	acrylic-coated cloth	■ Elongation at break	7.5 %
■ Total thickness	290 µm	■ Tensile strength	105 N/cm
■ Type of adhesive	thermosetting natural rubber	■ Temperature resistance (30 min)	180 °C
■ Adhesion to steel	4.6 N/cm	■ Mesh	145 count per square inch

Properties

■ Hand tearability	++	■ Suitable for die cutting	yes
■ Straight tear edges	++	■ Certified according to	all major OEMs
■ Easy to remove	yes	■ Abrasion resistance	++
■ Easy to write on	yes	■ Water resistance	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

Complies with LV 312-1 Dielectric strength.

For latest information on this product please visit <http://l.tesa.com/?ip=04657>

Page 1 of 1 / As of 07/23/15