

tesa® ACXplus 7055

ACXplus High Transparency 1000µm

PRODUCT INFORMATION

Product Description

tesa® ACXplus 7055 is a transparent acrylic core tape. It consists of a high-performance acrylic system and is primarily characterised by its Bonding Power, Stress Dissipation and its Temperature and Weather Resistance.

Due to the high transparency it is especially suitable for constructive bonding of transparent and translucent materials such as glass or acrylic.

The visco-elastic, solid acrylic core compensates different thermal elongation of bonded parts.

Main Application

Bonding of transparent and translucent materials in the following Industries:

- Sign manufacturing
- Deco Glass Panels
- Partition Walls

Technical Data

■ Backing material	solid acrylic	■ Elongation at break	1000 %
■ Colour	transparent	■ Temperature resistance long term	100 °C
■ Total thickness	1000 µm	■ Temperature resistance (20 min)	200 °C
■ Type of adhesive	pure acrylic		

Adhesion to

■ Steel (initial)	15 N/cm	■ Steel (after 3 days)	24 N/cm
■ Aluminium (initial)	13 N/cm	■ Aluminium (after 3 days)	24 N/cm
■ Glass (initial)	16 N/cm	■ Glass (after 3 days)	24 N/cm
■ PMMA (initial)	13 N/cm	■ PMMA (after 3 days)	17 N/cm

Properties

■ Tack	+	■ Softener resistance	o
■ Ageing resistance (UV)	++	■ Static shear resistance at 23°C	++
■ Humidity resistance	++	■ Static shear resistance at 70°C	+
■ Resistance to chemicals	++	■ T-block	+

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

tesa® ACXplus 7055

ACXplus High Transparency 1000µm

PRODUCT INFORMATION

Additional Info

PV 22 = White PE coated paper liner tesa® ACXplus branded
PV 24 = Blue filmic liner
Adhesion values to glass are not part of the product specification.

tesa® ACXplus 7055 is recognized according to UL Standard 746C. UL File QQQW2.E309290

For latest information on this product please visit <http://l.tesa.com/?ip=07055>

Page 2 of 2 / As of 07/23/15