

## tesa Softprint® 53417 FE

Plate mounting tape for photopolymer plates in flexographic printing

Double-sided foam tape

The soft foam makes this the ideal solution in printing screens and line work.

### Foam Properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

### Adhesive Properties

- Low tack surface characteristics
- Secure plate bonding with excellent resistance to edge lifting
- Excellent tape bonding towards cylinder/sleeve side
- Solvent resistance

### Additional Properties

- Compensating product design for demanding sleeve/cylinder surfaces.
- Structured PP liner
- Color indicates foam hardness

## Main Application

Mounting of 1.14 mm (0.45") and 1.70 mm (0.067") flexographic printing plates onto steel / aluminum / PU cylinders and sleeves.

## Technical Data

▪ Backing material	PE foam with film lamination	▪ Type of adhesive	tackified acrylic
▪ Color	red	▪ Type of liner	PP
▪ Total thickness	430 µm	▪ Logo colour	red
▪ Thickness category	380 µm	▪ Hardness	soft

For latest information on this product please visit <http://l.tesa.com/?ip=53417>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.