

## tesa Softprint® 72428 FE

### Foam plate mounting tape: CLASSIC Product Design

Double-sided foam tape

#### Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

#### Adhesive properties

- Low tack surface characteristics
- Best plate bonding
- Easy plate demounting
- Sufficient tape bonding towards sleeve side

#### Additional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted

## Main Application

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

## Technical Data

|                      |                              |                 |       |
|----------------------|------------------------------|-----------------|-------|
| ▪ Backing material   | PE foam with film lamination | ▪ Type of liner | PP    |
| ▪ Total thickness    | 550 µm                       | ▪ Logo colour   | green |
| ▪ Thickness category | 500 µm                       | ▪ Hardness      | hard  |
| ▪ Type of adhesive   | tackified acrylic            |                 |       |

For latest information on this product please visit <http://l.tesa.com/?ip=72428>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.