

tesa Softprint® 73426 FE

Foam plate mounting tape: FLEX Product Design

Double-sided foam tape

Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

Adhesive properties

- Low tack surface characteristics
- Best plate bonding
- Easy plate demounting
- Excellent tape bonding towards sleeve side

Additional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves

Main Application

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Data

▪ Backing material	PE foam with film lamination	▪ Type of liner	PP
▪ Total thickness	550 µm	▪ Logo colour	blue
▪ Thickness category	500 µm	▪ Hardness	medium-hard
▪ Type of adhesive	tackified acrylic		

For latest information on this product please visit <http://l.tesa.com/?ip=73426>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.