

## tesa® ACX<sup>plus</sup> 70730

ACX<sup>plus</sup> High Resistance 2.900µm

tesa® ACX<sup>plus</sup> 70730 is a black acrylic foam tape. It consists of a high-performance acrylic system and due to its unique components it combines a very good temperature resistance with an outstanding cold shock resistance. It is designed for permanent bonding applications especially in combination with the tesa Adhesion Promoters. The visco-elastic, foamed acrylic core compensates different thermal elongation of bonded parts.

## Main Application

Bonding of panels and decorative elements in the following Industries:

- Automotive
- Solar
- Elevator
- Production Equipment
- Transportation

## Technical Data

▪ Backing material	foamed acrylic	▪ Type of adhesive	pure acrylic
▪ Color	deep black	▪ Elongation at break	1000 %
▪ Total thickness	2900 µm		

## Adhesion to

▪ Steel (initial)	15.0 N/cm	▪ Steel (after 3 days)	44.0 N/cm
▪ Aluminium (initial)	15.0 N/cm	▪ Aluminium (after 3 days)	38.0 N/cm
▪ Glass (initial)	30.0 N/cm	▪ Glass (after 3 days)	39.0 N/cm

## Properties

▪ Temperature resistance short term	220 °C	▪ Softener resistance	● ●
▪ Temperature resistance long term	120 °C	▪ Static shear resistance at 23°C	● ● ● ●
▪ Tack	● ●	▪ Static shear resistance at 70°C	● ● ● ●
▪ Ageing resistance (UV)	● ● ● ●	▪ L-jig	● ● ● ●
▪ Humidity resistance	● ● ● ●	▪ T-block	● ● ● ●
▪ Resistance to chemicals	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

## Additional Information

PV 24 = Blue filmic liner

For latest information on this product please visit <http://l.tesa.com/?ip=70730>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.