



64006 AÇILDIĞINDA İZ BIRAKAN KOLİ BANDI

tesa® 64006 koli bandı, müşterinin bireysel markasını belirgin bir şekilde kutu üstünde taşımalarını sağlar.

tesa® 64006 özellikleri ile, kolilerin taşınması ve depolanması sırasında karışıklıkların azaltılmasına yardımcı olur. Bireysel baskı müşteri taleplerine göre geliştirildiğinden ve yalnızca tek müşteri için mevcut olduğundan; özel baskı prosesi ve kalite standartları sebebiyle, daha yüksek düzeyde bireysel güvenliği sağlamaktadır.

Açılmaya karşı koruma etkisi iki adımda çalışır:

tesa® 64006 bant kutudan çıkarıldığında "AÇILDI" anlamına gelen bir iz bırakır.

Çıkarılmaya işaret eden "AÇILDI" mesajı, kutunun yeniden kapatılmasından sonra da net bir şekilde görünür kalır.

Ana Uygulamalar:

Bu özellik, tesa® 64006'yı özellikle değerli veya gizli içeriğe sahip karton/kolilerin kapatılması için uygun kılar:

- Elektronik ürünler
- Yüksek değerli / markalı giyim eşyaları
- Tütün ürünleri
- Belgeler

Teknik Bilgiler:

- Taşıyıcı malzemesi: BOPP
- Toplam kalınlık: 62 µm
- Yapışkan türü: Su bazlı akrilik
- Çeliğe yapışma: 2.8 N/cm
- Kopma anındaki uzama: 150%
- Çekme direnci: 42 N/cm



tesa® 64006

Printed tamper evident carton sealing tape

tesa® 64006 is a tamper evident providing carton sealing tape with a customer individual imprint. With its characteristics tesa® 64006 helps to reduce pilferage during transport and storage of carton boxes.

The imprint ensures a higher level of individual security sealing as the artwork is developed according to customer demands and due to the special printing process and quality standards only available for this single customer.

tesa® 64006 is designed to avoid unnoticed opening and reclosure of carton boxes.

The tamper evident effect works in two steps:

- When tesa® 64006 is removed from the box, the product leaves the message "OPENED" in different languages on the carton.
- The tamper evident message "OPENED" remains clearly visible also after re-closure of the box.

The tamper evident effect may also be achieved through a complete carton fibre tear-out, which makes a re-closure impossible.

Colour: yellow, blue

The character is printed on the adhesive side (20% of printed surface is recommended) and shines through the tape in black.

Main Application

These characteristic makes tesa® 64006 especially suitable for the closure of cartons with valuable or confidential content as:

- Electronic products
- High value / branded clothing
- Tobacco products
- Documents

Technical Data

▪ Backing material	BOPP	▪ Adhesion to steel	2.8 N/cm
▪ Total thickness	62 µm	▪ Elongation at break	150 %
▪ Type of adhesive	water-based acrylic	▪ Tensile strength	42 N/cm

Properties

▪ Automatic application	yes	▪ Manual application	yes
-------------------------	-----	----------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=64006>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 64006

Printed tamper evident carton sealing tape

Additional Information

It has to be pointed out that on very lower carton qualities the adhesion should be tested and that the tamper evident effect (legible message or fibre tear) cannot be guaranteed.

Value "adhesion/steel": no parameter of the specification, not measurable.

Please note "total thickness" for blue coloured tape is 67µm.

For latest information on this product please visit <http://l.tesa.com/?ip=64006>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.