

tesa® extra Power Universal

Product Information



BNR 56348, 56338, 56389, 56388, 56380, 56490, 56396

Product Description

tesa[®] extra Power Universal is a versatile duct tape with high bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

٠	Backing material	PE-film with PET-	٠	Total thickness	215 µm
		filament			
•	Type of adhesive	synthetic rubber			



tesa® extra Power Universal

Product Information

Properties/Performance Values

• • • • •	Tensile strength Adhesive strength Ageing resistance (UV) Application temperature from Application temperature to Applicationfield Area of use	100 N/cm High adhesion yes 10 °C 50 °C Garden, Garage, Car, Home In- and Outdoor	•	Ozone resistance Residue free removal Reusable Solvent free Spare part service Suitable surfaces	yes no yes no Even wood, Tiles, Most plastics, Glass, Metal
•	Batteries included	no	٠	Tear resistance	yes
•	Batteries required Ecofriendly packaging	no no	•	Temperature resistance Temperature resistance max.	yes 95 °C
•	Hand tearability Hazard material	yes no	•	Tensibility UV-resistant	19 % yes
•	Humidity resistance Material	yes PE (polyethylene)	•	Water resistance Waterproof	yes yes
•	Oil and grease resistance	yes	٠	Writable	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

