



tesa[®] 51235

Product Information



Premium strength tear tape

Product Features

- Excellent tack
- Excellent adhesion and shear resistance on a variety of corrugated and solid cardboard surfaces
- Strong backing
- The product is recommended for high unwinding speeds in automatic production.
- Due to a co-extruded PP/PE backing tesa[®] 51235 exhibits an excellent and unique tear performance despite its relatively low thickness.

tesa[®] 51235 is a premium self-adhesive tensilised polypropylene tear strip with a synthetic rubber adhesive system.

Application Fields

- for medium to heavy grades of solid board and double-wall corrugated cardboard
- Recommended for automatic production

Product Construction

- | | | | |
|--------------------|------------------|--------------------|------|
| • Type of adhesive | synthetic rubber | • Backing material | MOPP |
| • Total thickness | 111 µm | | |

Product Properties/Performance Values

- | | |
|--------------------|----------|
| • Tensile strength | 180 N/cm |
|--------------------|----------|



tesa® 51235

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=51235>