



tesa® Professional 4398 Plastering Facade Cloth Tape



Product Information

Plastering Facade Cloth Tape

Product Description

With the tesa® Plastering Facade Cloth Tape, it takes no time at all to safely mask any areas that need to be protected during plastering work. That way, it can be nicely fitted to any part of the facade you need to cover so you can focus on the plastering task at hand sooner.

The natural rubber adhesive offers the familiar adhesive strength of tesa® products.

Product Features

- As it provides UV resistance for up to 10 days, the facade tape is well suited for basic outdoor plastering or painting tasks.
- It allows fast and effortless removal.
- After the work is done, the tape can be removed effortlessly and fast.
- The blue tape is a time-saver at most construction sites.
- With its ease of use, the fabric tape can be stretched for up to 20% of its length and torn off by hand.

Application Fields

- Easy and reliable protection for outdoor surfaces
- Sunlight is no problem: UV resistance for up to 10 days with residue-free removal
- Good handling through tensile strength, effortless to tear off by hand
- Saves time during work, can be taken off fast and without any effort
- Tape composition: backing material = cloth, adhesive = natural rubber
- Available sizes: 25m:30mm, 25m:50mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 260 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|-------------------------------|--------------------------|
| • Elongation at break | 20 % | • Mesh | 55 count per square inch |
| • Tensile strength | 55 N/cm | | |
| • Hand tearability | very good | • Suitable for rough surfaces | good |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 5 N/cm |
|---------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=04398>



tesa[®] Professional 4398 Plastering Facade Cloth Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04398>